



Figure 4: Effect of query expansion by adding nearby terms in W_p (1) in traditional language models (Model 1 [4] with Jelinek-Mercer smoothing) for W3C, CERC and TU benchmarks.

APPENDIX

The derivative of (3) w.r.t. bias term b_c equals

$$\frac{\partial L(W_p, W_c, b_c)}{\partial b_c} = -\frac{1}{m} \left(\sum_{i=1}^m \frac{|d_{\max}|}{|d^{(i)}|} \sum_{j=1}^{|C|} P(c_j | d^{(i)}) \frac{\partial \log(P(c_j | w_1^{(i)}, \dots, w_n^{(i)}))}{\partial b_c} \right)$$

and w.r.t. an arbitrary matrix parameter θ (W_p or W_c):

$$\frac{\partial L(W_p, W_c, b_c)}{\partial \theta} = -\frac{1}{m} \left(\sum_{i=1}^m \frac{|d_{\max}|}{|d^{(i)}|} \sum_{j=1}^{|C|} P(c_j | d^{(i)}) \frac{\partial \log(P(c_j | w_1^{(i)}, \dots, w_n^{(i)}))}{\partial \theta} \right) + \frac{\lambda}{m} \sum_{i,j} \theta_{i,j}.$$

Further differentiation for parameter θ (W_p , W_c or b_c):

$$\begin{aligned} \frac{\partial \log(P(c_j | w_1, \dots, w_n))}{\partial \theta} &= \frac{1}{P(c_j | w_1, \dots, w_n)} \frac{\partial P(c_j | w_1, \dots, w_n)}{\partial \theta} \\ &= \frac{\frac{\partial \tilde{P}(c_j | w_1, \dots, w_n)}{\partial \theta} Z_2 - \tilde{P}(c_j | w_1, \dots, w_n) \frac{\partial Z_2}{\partial \theta}}{Z_2^2} \\ \frac{\partial Z_2}{\partial \theta} &= \sum_k \frac{\partial \tilde{P}(c_k | w_1, \dots, w_n)}{\partial \theta} \\ \frac{\partial \tilde{P}(c_j | w_1, \dots, w_n)}{\partial \theta} &= \sum_k \frac{\partial P(c_j | w_k)}{\partial \theta} \prod_{i \neq k} P(c_j | w_i) \end{aligned}$$

For a given candidate c_j and word w_i , following (1) we have

$$\begin{aligned} P(c_j | w_i) &= \frac{\tilde{P}(c_j | w_i)}{Z_1} \\ &= \frac{\exp((\sum_{k=1}^e W_{c_j,k} W_{p_{k,i}}) + b_{c_j})}{\sum_{l=1}^{|C|} \exp((\sum_{k=1}^e W_{c_l,k} W_{p_{k,i}}) + b_{c_l})} \end{aligned}$$

and consequently, with $\mathbf{W}_{p_i}^\top$ denoting the i -th column of matrix W_p ,

$$\begin{aligned} \frac{\partial P(c_j | w_i)}{\partial \mathbf{W}_{c_j}} &= \frac{(Z_1 - \tilde{P}(c_j | w_i)) \tilde{P}(c_j | w_i) \mathbf{W}_{p_i}^\top}{Z_1^2} \\ \frac{\partial P(c_j | w_i)}{\partial b_{c_j}} &= \frac{(Z_1 - \tilde{P}(c_j | w_i)) \tilde{P}(c_j | w_i)}{Z_1^2} \quad (7) \\ \frac{\partial P(c_j | w_i)}{\partial \mathbf{W}_{p_i}^\top} &= \frac{(\mathbf{W}_{c_j} - \sum_{l=1}^{|C|} \mathbf{W}_{c_l}) \tilde{P}(c_j | w_i)}{Z_1} \end{aligned}$$

As can be seen in (7), the distributed representations of candidates c_j at time $t+1$ are updated using the representation of words w_i at time t and vice versa.

REFERENCES

- [1] The knowledge-based economy. Techn. report, Organisation for Economic Co-operation and Development, 1996.
- [2] P. Bailey, A. P. De Vries, N. Craswell, and I. Soboroff. Overview of the TREC 2007 enterprise track. In *TREC*, 2007.
- [3] K. Balog. *People Search in the Enterprise*. PhD thesis, University of Amsterdam, 2008.
- [4] K. Balog, L. Azzopardi, and M. de Rijke. Formal models for expert finding in enterprise corpora. In *SIGIR*, pages 43–50, 2006.
- [5] K. Balog, L. Azzopardi, and M. de Rijke. A language modeling framework for expert finding. *IPM*, 45:1–19, 2009.
- [6] K. Balog, Y. Fang, M. de Rijke, P. Serdyukov, and L. Si. Expertise retrieval. *Found. & Tr. in Information Retrieval*, 6(2-3):127–256, 2012.
- [7] I. Becerra-Fernandez. Role of artificial intelligence technologies in the implementation of People-Finder knowledge management systems. *Knowledge-Based Systems*, 13(5):315–320, 2000.
- [8] Y. Bengio, R. Ducharme, P. Vincent, and C. Janvin. A neural probabilistic language model. *JMLR*, 3:1137–1155, 2003.
- [9] Y. Benjamini and Y. Hochberg. Controlling the false discovery rate: a practical and powerful approach to multiple testing. *JSTOR*, pages 289–300, 1995.
- [10] R. Berendsen, M. de Rijke, K. Balog, T. Bogers, and A. van den Bosch. On the assessment of expertise profiles. *JASIST*, 64(10):2024–2044, 2013.
- [11] L. Bottou. Large-scale machine learning with stochastic gradient descent. In *COMPSTAT*, pages 177–186. Springer, 2010.
- [12] C. Burges, T. Shaked, E. Renshaw, A. Lazier, M. Deeds, N. Hamilton, and G. Hullender. Learning to rank using gradient descent. In *ICML*, pages 89–96, 2005.
- [13] Y. Cao, J. Liu, S. Bao, and H. Li. Research on Expert Search at Enterprise Track of TREC 2005. In *TREC*, pages 2–5, 2005.
- [14] R. Collobert, J. Weston, L. Bottou, M. Karlen, K. Kavukcuoglu, and P. Kuksa. Natural language processing (almost) from scratch. *JMLR*, 12(Aug):2493–2537, 2011.
- [15] N. Craswell, D. Hawking, A.-M. Vercoustré, and P. Wilkins. P@optic expert: Searching for experts not just for documents. In *Ausweb Poster Proceedings*, pages 21–25, 2001.
- [16] N. Craswell, A. P. de Vries, and I. Soboroff. Overview of the TREC 2005 enterprise track. In *TREC*, 2005.
- [17] T. H. Davenport and L. Prusak. *Working Knowledge*. Harvard Business Review Press, 1998.
- [18] S. C. Deerwester, S. T. Dumais, and R. A. Harshman. Indexing by latent semantic analysis. *JASIS*, 1990.

- [19] G. Demartini, J. Gaugaz, and W. Nejdl. A vector space model for ranking entities and its application to expert search. In *ECIR*, pages 189–201. Springer, 2009.
- [20] L. Deng, X. He, and J. Gao. Deep stacking networks for information retrieval. In *ICASSP*, pages 3153–3157, 2013.
- [21] H. Fang and C. Zhai. Probabilistic models for expert finding. In *ECIR*, pages 418–430, Berlin, Heidelberg, 2007. Springer-Verlag.
- [22] Y. Fang and A. Godavarthy. Modeling the dynamics of personal expertise. In *SIGIR*, pages 1107–1110, 2014.
- [23] Y. Fang, L. Si, and A. P. Mathur. Discriminative models of integrating document evidence and document-candidate associations for expert search. In *SIGIR*, pages 683–690, 2010.
- [24] K. Fatahalian, J. Sugerma, and P. Hanrahan. Understanding the efficiency of gpu algorithms for matrix-matrix multiplication. In *SIGGRAPH HWS*, pages 133–137. ACM, 2004.
- [25] X. Glorot and Y. Bengio. Understanding the difficulty of training deep feedforward neural networks. In *AISTATS*, pages 249–256, 2010.
- [26] G. E. Hinton. Learning distributed representations of concepts. In *8th Annual Conference of the Cognitive Science Society*, volume 1, page 12, Amherst, MA, 1986.
- [27] T. Hofmann. Probabilistic latent semantic indexing. In *SIGIR*, pages 50–57. ACM, 1999.
- [28] P.-s. Huang, N. M. A. Urbana, X. He, J. Gao, L. Deng, A. Acero, and L. Heck. Learning deep structured semantic models for web search using clickthrough data. In *CIKM*, pages 2333–2338, 2013.
- [29] P. Indyk and R. Motwani. Approximate nearest neighbors: towards removing the curse of dimensionality. In *STOC*, pages 604–613. ACM, 1998.
- [30] M. Karimzadehgan and C. Zhai. Estimation of statistical translation models based on mutual information for ad hoc information retrieval. In *SIGIR*, pages 323–330. ACM, 2010.
- [31] R. Kiros, R. Salakhutdinov, and R. Zemel. Multimodal neural language models. In *ICML*, pages 595–603, 2014.
- [32] J. Kruger and D. Dunning. Unskilled and unaware of it: how difficulties in recognizing one’s own incompetence lead to inflated self-assessments. *J. Personality and Social Psych.*, 77(6):1121, 1999.
- [33] J. Krüger and R. Westermann. Linear algebra operators for gpu implementation of numerical algorithms. *ACM Transactions on Graphics*, 22(3):908–916, 2003.
- [34] H. Li and J. Xu. Semantic matching in search. *Found. & Tr. in Information Retrieval*, 7(5):343–469, June 2014.
- [35] T.-Y. Liu. *Learning to Rank for Information Retrieval*. Springer, 2011.
- [36] C. MacDonald and I. Ounis. Voting for candidates: adapting data fusion techniques for an expert search task. In *CIKM*, pages 387–396, 2006.
- [37] C. Macdonald and I. Ounis. Expert search evaluation by supporting documents. In *ECIR*, pages 555–563. Springer, 2008.
- [38] M. T. Maybury. Expert finding systems. Techn. Report MTR-06B000040, MITRE, 2006.
- [39] D. W. McDonald and M. S. Ackerman. Expertise recommender. In *CSCW*, pages 231–240, 2000.
- [40] T. Mikolov, M. Karafiat, L. Burget, J. Cernocky, and S. Khudanpur. Recurrent neural network based language model. In *Interspeech*, pages 1045–1048, 2010.
- [41] T. Mikolov, K. Chen, G. Corrado, and J. Dean. Distributed representations of words and phrases and their compositionality. In *NIPS*, pages 3111–3119, 2013.
- [42] T. Mikolov, G. Corrado, K. Chen, and J. Dean. Efficient estimation of word representations in vector space. arXiv 1301.3781, 2013.
- [43] A. Mnih and G. Hinton. Three new graphical models for statistical language modelling. In *ICML*, pages 641–648, 2007.
- [44] A. Mnih and G. Hinton. A scalable hierarchical distributed language model. In *NIPS*, pages 1081–1088, 2008.
- [45] A. Mnih and K. Kavukcuoglu. Learning word embeddings efficiently with noise-contrastive estimation. In *NIPS*, pages 2265–2273, 2013.
- [46] G. Montavon, G. B. Orr, and K.-R. Müller. *Neural Networks: Tricks of the Trade*. Springer, 2012.
- [47] C. Moreira, B. Martins, and P. Calado. Using rank aggregation for expert search in academic digital libraries. In *Simpósio de Informática, INForum*, pages 1–10, 2011.
- [48] J. Pennington, R. Socher, and C. D. Manning. GloVe: Global Vectors for Word Representation. In *EMNLP*, pages 1532–1543, 2014.
- [49] D. Petkova and W. B. Croft. Hierarchical language models for expert finding in enterprise corpora. In *ICTAI ’06*, pages 599–606, 2006.
- [50] W. W. Powell and K. Snellman. The knowledge economy. *Annual review of sociology*, pages 199–220, 2004.
- [51] D. Rumelhart, G. Hinton, and R. Williams. Learning internal representations by back propagation. In *Parallel Distributed Processing*, pages 318–362. MIT Press, 1986.
- [52] J. Rybak, K. Balog, and K. Nørvgå. Temporal expertise profiling. In *ECIR*, pages 540–546. Springer, 2014.
- [53] R. Salakhutdinov and G. Hinton. Semantic hashing. *Int. J. Approximate Reasoning*, 50(7):969–978, 2009.
- [54] P. Serdyukov and D. Hiemstra. Modeling documents as mixtures of persons for expert finding. In *ECIR*, pages 309–320. Springer, 2008.
- [55] P. Serdyukov, H. Rode, and D. Hiemstra. Modeling multi-step relevance propagation for expert finding. In *CIKM*, pages 1133–1142, 2008.
- [56] C. Shannon. A mathematical theory of communication. *Bell System Technical J.*, 27:379–423, 623–656, 1948.
- [57] J. A. Shaw, E. A. Fox, J. A. Shaw, and E. A. Fox. Combination of multiple searches. In *TREC*, pages 243–252, 1994.
- [58] Y. Shen, X. He, J. Gao, L. Deng, and G. Mesnil. A latent semantic model with convolutional-pooling structure for information retrieval. In *CIKM*, pages 101–110, 2014.
- [59] M. D. Smucker, J. Allan, and B. Carterette. A comparison of statistical significance tests for information retrieval evaluation. In *CIKM*, pages 623–632. ACM, 2007.
- [60] P. Sorg and P. Cimiano. Finding the right expert: Discriminative models for expert retrieval. In *KDIR*, pages 190–199, 2011.
- [61] TREC. Enterprise Track, 2005–2008.
- [62] D. van Dijk, M. Tsagkias, and M. de Rijke. Early detection of topical expertise in community question and answering. In *SIGIR*, 2015.
- [63] V. Vapnik. *Statistical learning theory*, volume 1. Wiley New York, 1998.
- [64] M. D. Zeiler. Adadelta: An adaptive learning rate method. *CoRR*, abs/1212.5701, 2012.