























- Journal of Approximate Reasoning*, 50(7):969–978, 2009.
- [29] Y. Shen, X. He, J. Gao, L. Deng, and G. Mesnil. A latent semantic model with convolutional-pooling structure for information retrieval. In *CIKM 2014*, pages 101–110. ACM, 2014.
- [30] K. M. Svore and C. J. Burges. A machine learning approach for improved BM25 retrieval. In *CIKM 2009*, pages 1811–1814. ACM, 2009.
- [31] P. D. Turney. Measuring semantic similarity by latent relational analysis. In *IJCAI'05*, pages 1136–1141, 2005.
- [32] L. Van der Maaten and G. Hinton. Visualizing high-dimensional data using t-SNE. *J. Machine Learning Research*, 9:2579–2605, 2008.
- [33] Q. Wang, J. Xu, H. Li, and N. Craswell. Regularized latent semantic indexing. In *SIGIR 2011*, pages 685–694. ACM, 2011.
- [34] X. Wei and W. B. Croft. LDA-based document models for ad-hoc retrieval. In *SIGIR 2006*, pages 178–185. ACM, 2006.
- [35] W. Wu, Z. Lu, and H. Li. Learning bilinear model for matching queries and documents. *The Journal of Machine Learning Research*, 14(1):2519–2548, 2013.
- [36] W.-t. Yih, K. Toutanova, J. C. Platt, and C. Meek. Learning discriminative projections for text similarity measures. In *CoNLL*, pages 247–256. ACL, 2011.